

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number  
**WO 2004/055805 A1**

(51) International Patent Classification<sup>7</sup>: **G11B 17/04**

**COSTEMORE D'ARC, Stéphane** [FR/BE]; rue Emile François 40, B-1474 Ways (BE).

(21) International Application Number:  
PCT/BE2003/000215

(74) Agents: **OVERATH, Philippe** et al.; Cabinet Bede S.A., Boulevard Lambertmont 140, B-1030 Brussels (BE).

(22) International Filing Date:  
10 December 2003 (10.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2002/0736 18 December 2002 (18.12.2002) BE

(71) Applicant (for all designated States except US): **STAAR SOCIETE ANONYME** [BE/BE]; Chaussée de Roodebeek 137-143, B-1200 Bruxelles (BE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **D'ALAYER** de

[Continued on next page]

(54) Title: **TRANSFER DEVICE FOR INFORMATION CARRIERS**



(57) Abstract: The device ensures transfer of information carriers of different dimensions thanks to a single loading device including detection means (32) associated to linking means (40). Upon the insertion of an information carrier, the linking means (40) cooperates with a projection (50A, 50B) set in relation with the size of the inserted information carrier, this projection being supported by a slider (52) actuating clamping and driving means to ensure the setting of the inserted information carrier in its operative position. Thus, the synchronization between these clamping and driving means is made in relation with the size of said carrier.